Downlight MD-990, 13W, 230V, Satin, IP44

Item: 9974329

MALMBERGS

Product information

Recessed mounting. Connection to fast terminal block 4x2.5 mm². The luminaire is approved for mounting on normally fl ammable surfaces and directly in insulation material. Dimmable with transistor dimmer with trailing edge technology (RC). S-marked. Dimmable. Double insulation.

Specifications

Energy efficiency class	A++-A
Height	70 mm
Mounting depth	65 mm
Colour consistency	3 SDCM
Outer diameter	85 mm
For hole (Ø)	75 mm
Colour temperature	2600K
Beam angle	40°
Luminous intensity	1586cd
Luminous flux	851lm
Power	13W
Colour	Satin
Voltage	230V
IP rating	IP44
Colour rendering index (CRI)	Ra=92

Malmbergs Elektriska AB (publ)
PO Box 144, SE-692 23 Kumla, SWEDEN
Phone: +46 (0)19 58 77 00 | Fax: +46 (0)19 57 11 77 | info@malmbergs.com

Downlight MD-990, 13W, 230V, Satin, IP44

Item: 9974329

MALMBERGS

Malmbergs Elektriska AB (publ)
PO Box 144, SE-692 23 Kumla, SWEDEN
Phone: +46 (0)19 58 77 00 | Fax: +46 (0)19 57 11 77 | info@malmbergs.com