Downlight Kit MD-315, LED, 230V, White, IP44

Item: 9974377

MALMBERGS

Product information

The kit contains of 3 downlights, 3 extension cables (1.5 m), 1 splitter (3 way) and 1 dimmable driver. For recessed mounting, with or without electrical installation box, or surface mounting together with surface mount housing. Incl. white outer ring.

Dimmable with transistor dimmer with trailing edge technology (RC). The luminaires are approved for mounting on normally flammable surfaces and directly in insulation material.

Specifications

Beam angle	90°
Colour	White
Colour consistency	3 SDCM
Colour rendering index (CRI)	Ra82
Colour temperature	2700K
Diameter	80 mm
Dims (ØxH)	80x22 mm
Energy efficiency class	A++-A
For hole	60 mm
IP rating	IP44, recessed/IP21, surface mounting
Luminous flux	3x255lm
Luminous intensity	3x150cd

Downlight Kit MD-315, LED, 230V, White, IP44

Item: 9974377

MALMBERGS

Mounting depth	18 mm.
Power	13W
Voltage	230V

Malmbergs Elektriska AB (publ)
PO Box 144, SE-692 23 Kumla, SWEDEN
Phone: +46 (0)19 58 77 00 | Fax: +46 (0)19 57 11 77 | info@malmbergs.com